

# 01

MERCURY SUPER VENTURA  
KT-950-0220-00

UNDERSTAND | INNOVATE | PROTECT

T: +44 (0) 1989 568 350  
F: +44 (0) 1989 568 351  
info@kirintec.com  
www.kirintec.com



## MERCURY SUPER VENTURA



### HIGH PERFORMANCE C-IED SYSTEM

Super Ventura takes the proven technology from Mercury Ventura and increases the frequency coverage up to 6 GHz and doubles the output power to 90 Watts.

Super Ventura is a mission proven, fully programmable C-IED jammer for portable use. Capable of defeating all current and likely future RCIED threats.

The system is a portable and flexible C-IED jammer designed with ultra-fast, powerful and versatile signal sources and is fully programmable between 20 MHz and 6 GHz. Super Ventura is provided with an omnidirectional antenna as standard or directional antenna if required.

### Key Features

90 Watts output

Fully programmable  
20 MHz – 6 GHz

- Dimensions:  
460mm x 230mm x 295mm
- Weight: 22.6 kg (excluding power)
- Operating frequency:  
20 MHz – 6 GHz
- Operating temperature range:  
as standard: -20°C to +55°C



T: +44 (0) 1989 568 350  
 F: +44 (0) 1989 568 351  
 info@kirintec.com  
 www.kirintec.com

MERCURY SUPER VENTURA  
 KT-950-0220-00

UNDERSTAND | INNOVATE | PROTECT

02

## Specifications

- Dimensions  
460mm x 230mm x 295mm
- Weight  
22.6 kg (excluding power)

## Colour Options



Anthracite Grey



Black



Green



Sand

For more product information  
 scan this code:



System characteristics	SUPER VENTURA
RF power	90W
Voltage in	18 to 32 VDC
SUPER VENTURA Frequency Range	20 MHz – 6 GHz
Batteries	Detachable 2590 Li-ion
Operating temperature range as standard	-20°C to +55°C
IP 65 environmental protection	✓
Programmable	✓
Built-in self test	✓
Anti-Tamper	✓
Zeroize	✓
Antenna set	Omni or directional
Programming files and transfer device	✓
Battery charger	✓

## Mercury SUPER VENTURA

### Description

SUPER VENTURA Manpack ECM (Please contact us for advice on configuration.)  
 Please ask about incorporating Communications Through Inhibition (CTI)